



Quilosa Gold Effect Spray

This high-gloss effect spray gives a long-term look similar to polished gold to smooth surfaces. Not weather-resistant. Not resistant to abrasion, therefore not suitable to spray on objects for daily use. Suitable for all smooth surfaces like metal, wood, glass and many coatable plastics. Indispensable for constructors of fair booths, decorators, florists etc., but also for handicrafts at home, in courses and seminars.

Benefits

- Very good coverage
- Excellent adhesion
- Resistant to water and common household cleansers
- Effect of gloss can change by intense rubbing or wiping.
- Quick-drying
- Good flow, smooth surface
- Very high gloss
- Resistant to water, and household cleaners.

Characteristics

Contents : 400 ml

Base : acrylic co-polymers

Smell : solvent

Coverage : depends on colour of the ground- from 1,25 m²

Dust dry : After approximately 10 minutes

Tack free: After approximately 60 minutes

Cured: after approx.24 hours

Heat resistant : to 80°C

Storage/Warranty: 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)*

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. The can should have room temperature. Best results will be achieved during surrounding temperature of approx. 15-25°C. Test the colour at an invisible spot. To achieve excellent result apply a layer of primer. Before use, shake the can for 2 minutes. Distance to the surface to be treated approximately 25-30 centimeter. Apply the lacquer in several thin layers.

Do not use finishing coat clear lacquer. Do not spray over surfaces which are painted with synthetic resin lacquer.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind and in well-ventilated rooms. Follow the warning texts on the labels!

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

*10 years warranty-means products save their properties for 10 years from production time (exp. date shown on the can).

With the publication of this Technical Data Sheet, previous editions are no longer valid.